

DECLARATION OF PERFORMANCE

No. Nordkalk 1504 - CPR - 0356 R3 - 0/1,4 M

1. Unique identification code of the product-type: , *Limestone fine aggregate Nordkalk LK R3 - 0/1,4 M*

2. Intended use/es: Mortar used in buildings, roads and other civil engineering works

3. Manufacturer: Nordkalk AS, Faehlmanni tee 11a, Rakke, Lääne-Virumaa, 46301

5. System/s of AVCP: 2+

6a. Harmonised standard: EN 13139:2002+AC:2004

Notified body/ies: Tallinna Sertifitseerimisasutus OÜ reg. No 1504

Certificate of conformity of the factory production control no : 1504 - CPR - 0356

7. Declared performance/s:

The relevant characteristics	Performance
Particle Size	0 / 1,4
Particle size distribution	
<2,0 mm	100 %
<1,4 mm	95.... 99 %
<1,0 mm	75.... 95 %
<0,5 mm	50 80 %
<0,25 mm	30...65 %
<0,125 mm	< 50 %
<0, 063 mm	≤ 40 %
Fine particle content	≤ 40 %
Particle Density	2,52 - 2,72 Mg/m ³
Water absorption	< 1
Chlorides	< 0,02 %
Total Sulfur	< 0,1 %
Acid Soluble Sulfates	AS _{NR}
Radioactivity	I ≤ 1
Petrographic Description (raw material)	100 % limestone

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Piia Kirs, Quality manager
Rakke 01.03.2025





1504

*Nordkalk AS, Faehlmanni tee 11A, Rakke, Lääne - Virumaa 46301
Rakke plant*

13

No. Nordkalk 1504 - CPR - 0356 R3 - 0/1,4 M

EN 13139:2002+AC:2004
„Aggregates for mortar“

Nordkalk LK R3 - 0/1,4 M

Mortar used in buildings, roads and other civil engineering works

Characteristic	Product / performance
Particle Size	0 / 1,4
Fine particle content	≤ 40 %
Chlorides	< 0,02 %
Acid Soluble Sulfates	AS _{NR}
Total Sulfur	< 0,1 %
Radioactivity	I ≤ 1
<i>Petrographic Description (raw material)</i>	100 % limestone